

Hliníkové rampy



PS
BETON MACHINE
PSBETON.COM
+420 606 681 030



Brněnská 543

664 42 Brno-Modřice

www.psbeton.com

tel.: 00 420 606 681 030

psbeton@psbeton.com

Technická specifikace

HLINÍKOVÉ RAMPY

- Různé rozměry od 2 m do 5 m s nosností od 1,6t do 12,2t
- rampy viz foto č.1 nosnost 12,2 tun, délka 3,5 m

Kód zboží	Nosnost páru dle rozvoru			Délka mm.	Šířka mm.	Váha páru kg
	750	1000	1250			
H79/15	1685	1685	1685	1545	310	17,36
H79/20	1600	1600	1600	1950	310	20,96
H79/25	1360	1590	1600	2520	310	26,4
H79/30	1050	1180	1350	2920	310	30,4
H79/35	849	936	1036	3505	310	35,4
	1000	1250	1500			
H110/30	2790	3190	3450	3100	365	52
	1000	1500	2000			
H135/40	3200	3800	4800	4000	455	97
	1500	1750	2000			
H175/35	6960	7955	8719	3500	590	99
H175/40	6133	6880	7830	3990	590	140
H175/50	4274	4625	5037	4995	590	178
	1500	1750	2000			
H190/35	10934	12226	12226	3590	590	132
H190/40	8557	9601	10934	3990	590	152
H190/45	7029	7718	8557	4590	590	167
H190/50	5964	6453	7029	4995	590	184
	1500	1750	2000			
H220/40	12000	12000	12000	3990	605	176
H220/45	9600	12000	12000	4590	605	198,5
H220/50	8175	8800	9535	4995	605	220